

B236



Description

Adjustable

Cut Out

92mm

Diameter

100mm

Depth

85mm, 105mm (18w)

IP Rating

IP20

Colour

White

Black

Custom*

Kelvin

2700k, 3000k, 4000k

CRI

≥90, ≥97

SDCM

2 Step

Optics

18°, 25°, 40°, 60°

Accessories

Honeycomb Louvre, Frosted Filter

LED Power

4w, 9w, 13w, 18w

Dimming (Remote Driver)

Phase, Dali, Casambi, 1-10v*

Other Options

Dim-To-Warm 1800k-3000k*

Tunable White 2700k-5000k*



B236 - 4w

Lumens delivered

- ≥90 - 2700k - 484 lm*
- ≥90 - 3000k - 532 lm*
- ≥90 - 4000k - 562 lm*
- ≥97 - 2700k - 418 lm*
- ≥97 - 3000k - 428 lm*
- ≥97 - 4000k - 474 lm*

B236 - 9w

Lumens delivered

- ≥90 - 2700k - 1008 lm
- ≥90 - 3000k - 1109 lm
- ≥90 - 4000k - 1170 lm
- ≥97 - 2700k - 871 lm
- ≥97 - 3000k - 891 lm
- ≥97 - 4000k - 987 lm

B236 - 13w

Lumens delivered

- ≥90 - 2700k - 1329 lm
- ≥90 - 3000k - 1469 lm
- ≥90 - 4000k - 1556 lm
- ≥97 - 2700k - 1145 lm
- ≥97 - 3000k - 1186 lm
- ≥97 - 4000k - 1322 lm

B236 - 18w

Lumens delivered

- ≥90 - 2700k - 1789 lm
- ≥90 - 3000k - 1971 lm
- ≥90 - 4000k - 2094 lm
- ≥97 - 2700k - 1603 lm
- ≥97 - 3000k - 1686 lm
- ≥97 - 4000k - 1922 lm