



Linear 30





PROFILE SIZE:



TRIDONIC
LIGHT ENGINE

DALI
OPTIONAL

IP20
RATED

DIRECT
LIGHT


PHYSICAL CHARACTERISTICS:

LENGTH

- 1200mm
- 1500mm
- 1800mm
- 2000mm
- 2400mm
- 2700mm
- 3000mm
- Custom length

For custom lengths, LED Flex Module - 100mm increments.
Continuous lengths up to 3000mm then a junction is required.

JUNCTIONS



FINISH


- Texture Black
- Texture White
- Brushed Brass
- Gold Pearl
- Dark Bronze
- Texture Silver

- Custom Finish Please specify,

Custom finishes you can specify are powder coats, timber finishes and anodising. Contact us for more information.

CUSTOM SHAPE

Any shape can be produced using the junctions including prisms and pyramids. Draw a sketch below with dimensions required and send it to us for quoting.



ELECTRICAL CONFIGURATION:

TRIDONIC FLEX LIGHT ENGINE (Constant Voltage)

- 7 Watts / meter = 1200 lumens / meter
- 11 Watts / meter = 1800 lumens / meter
- 16 Watts / meter = 2500 lumens / meter
- Custom output required

DISTRIBUTION

Direct light only. 100° Diffused.

CCT

- 3000K Warm White
- 4000K Cool White
- 6500K Day Light
- Tunable White
- RGB (Different wattage applies)
- RGBW (Different wattage applies)

CRI

- CRI >80 (standard)
- CRI 90 (optional - fees apply)

IP RATING

IP20 (For indoor use only. Should not be used in wet areas)

DIMMING

- Non Dim - On/Off
- Phase Cut
- SwitchDIM
- DALI

CONTROL GEAR


Contessa constant voltage P/C dimmable driver
Tridonic constant voltage Non Dim driver
Tridonic One4All DALI constant voltage driver

WARRANTY


- 3 Years (standard)
- 5 Years (optional - fees apply)

MOUNTING OPTIONS:


Option 1 - Suspended with Bullets (standard)




Option 2 - Suspended with Canopies (RD)
(One end or both ends)



Option 3 - Suspended with Rods



Option 4 - Suspended with Centre Canopy



Option 5 - Surface Mounted



SUSPENSION PLACEMENT

Suspension mounts can be specified anywhere along the length of the linear however the standard is;

1000 - 2000mm long = 200mm in from each end

2100 - 3000mm long = 300mm in from each end

Custom placement *Please specify,*

SUSPENSION LENGTH

Suspension lengths can be specified longer however the standard is;

Wires = 2000mm long (adjustable)

Rod = 1500mm continuous before join



Custom length *Please specify,*

CANOPY OPTIONS: *(For option 2 & 3 above)*



38mm Mini-Mount
Recessed Cut-out 32mm





70mm Recessed
Cut-out 51mm



70mm Surface



100mm Surface





CANOPY FINISHES

Recessed Mini-Mount 38mm, 70mm and 70mm surface canopies are available in all finishes.

100mm Round and 500mm rectangular centre mount canopies are available in Texture Black, Texture White and Gold Pearl or custom powder coat colours.

Centre Mount Canopy *(For option 4 above)*
Available in Black, White & Gold Pearl



Code Generator:

Product	Length	Finish	Output	CCT	Mounting	Driver
LINEAR 30	1200MM - 12	Texture Black - BL	1200 lm/m - 7W	3000K - 3K	Option 1 - M1	On/Off - STA
	1500MM - 15	Texture White - WH	1800 lm/m - 11W	4000K - 4K	Option 2 - M2	Phase Cut - PC
	1800MM - 18	Gold Pearl - GP	2500 lm/m - 15W	6500K - 5K	Option 3 - M3	DALI - DA
	2000MM - 20	Brushed Brass - BB	CUSTOM - C/O	Tunable White - TW	Option 4 - M4	SwitchDIM - SwD
	2400MM - 24	Dark Bronze - DB		RGB - RGB	Option 5 - M5	
	2700MM - 27	Silver - SIL		RGBW - RGBW	CUSTOM - C/M	
	3000MM - 30	CUSTOM - C/F				
	CUSTOM - C/L					
LP-3030						

When specifying custom details e.g. shape, length & finish, please include the details in the comments section of the online project quote request function on our website or include in the lighting schedule.