Lindri Aluminium Black

Garden Bollard Spike Light

Name	Lindri				
Material	Aluminium				
Colour	Poly Powder Coated Black				
IP Rating	IP65				
Colour Temp	3000k 4000k 5500k				
IK Rating	IK08				
Installation Type	Ground - Spike				
Diffuser Type	Perspex				
Lamp Base	Built in LED				
Max Wattage	3w				
Cable Length	1000mm				
Protection Class	3 (Low Voltage - No Earth Required)				
Lamp Expectancy	<30,000hrs*				
CRI	CRI>80				
SDCM	<6				
UGR	<19				
Dimmable	No				
Warranty	3 Years Replacement*				













Product Ordering

Image	Part Number	Colour Temp	Lumens	Input Voltage	Beam Angle	Included LED	Barcode
	HV1516T-BLK-24V	3000K 4000K 5500K	80lm 90lm 85lm	24v DC	120°	TRI Colour 3w Built in LED	9350418040442



Related Products Dimensions 90x25 HV1517T-BLK-24V 25‡Ⅲ 600 210

HV1518T-BLK-24V

Optional Havit Compatible Accessories

Image	Part Number	Description						
24v Drivers								
And State of the Part of the P	24v DC LED Drivers	See Catalogue or Website for full range of 24v DC LED Drivers						
Weatherproof Connectors								
	HV9911	Small IP67 Weatherproof Connector						
	HV9912	Medium IP67 Weatherproof Connector						
A	HV9913	Large IP67 Weatherproof Connector						

